

## MATERIAL SAFETY DATA SHEET

### TRADESMAN GAP FILLER

DATE: 26/08/2011

#### 1. COMPANY & PRODUCT INFORMATION

Supplier:	Macsim Australia Pty Ltd
Address:	10 Wonderland Drive Eastern Creek, NSW, 2766
Phone:	(+612) 9881 2400
Fax:	(+612) 9881 2444
Product Name:	Tradesman Gap Filler
Classification:	Acrylic Gap Filler
Product Use:	Tradesman Gap filler is a one part, gun applied, water-based acrylic sealant that cures to a flexible and tough rubber with good adhesion to porous sealant that can be easily cleaned up with water. These dispersion acrylic sealants are far more superior if compared to other caulking compound, such as butyl mastic, oil based mastic etc.
Product Code:	53TGF

#### 2. HAZARDS IDENTIFICATION

Hazard Description:	Not applicable
Hazardous information for human and environment	
Ingestion:	None known.
Skin contact:	Uncured product contact may irritate the skin.
Eye contact:	Uncured product contact irritates eyes.
Inhalation:	May cause mild respiratory irritation.

#### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS NO.	APPROX WT%
Plasticizer	117-81-7	< 5%
Ethylene glycol	107-21-1	1-10%
Mineral Spirits	64742-48-9	1-5%

#### 4. FIRST AID MEASURES

After Swallowing:	Seek medical attention immediately.
After Eye Contact:	Immediately flush with water, seek medical advice if necessary.
After Skin Contact:	Wipe with paper towel and immediately clean with water and soap.
After Inhalation:	Move patient to fresh air. If breathing becomes difficult seek medical information immediately.
Note:	Take off all contaminated clothing immediately.

## MATERIAL SAFETY DATA SHEET

### TRADESMAN GAP FILLER

DATE: 26/08/2011

#### 5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:	Use water, CO <sub>2</sub> , foam, dry powder and all standard fire-fighting media depending on fire conditions.
Unsuitable extinguishing media:	Unknown.
Fire Fighting:	Wear protective clothing and suitable breathing apparatus.
Hazardous Decomposition:	Not specified.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Safety Precautions:	See personal protection recommendations in section 8.
Environmental Protection:	Keep spilled product out of sewers/ drains, ground water and water systems.
Measures for cleaning up:	Wipe or soak up spilled product and place in a container for disposal.

#### 7. HANDLING AND STORAGE

Handling Precautions:	Ensure good ventilation during processing. Wear safety shoes.
Protection against fire / explosion:	General rules of fire prevention should be observed.
Storage Precautions:	Keep container tightly closed and dry.
Caution:	Extremely heavy in drum form if product packed in 200L drum.

#### 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Workplace Exposure:	Not Applicable
Personal Protection	
Hygienic Measures:	Always wash hands before eating, drinking and when leaving the workplace.
Respiratory Protection:	None required if used in well ventilated areas.
Hand Protection:	Always wear protective gloves.
Eye Protection:	Always wear protective or safety glasses.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

General Information	
Form:	Paste
Colour:	White
Odour:	Mild Acrylic Odour
Change in Condition	
Boiling point/ range:	>100°C
Flash Point:	Not determined
Ignition Temperature:	Not determined
Volatile % (25°C):	<45%
Viscosity:	Not Indicated.
Solubility in water:	Yes

## MATERIAL SAFETY DATA SHEET

### TRADESMAN GAP FILLER

DATE: 26/08/2011

#### 10. CHEMICAL STABILITY AND REACTIVITY INFORMATION

Conditions to avoid:	None known
Materials to avoid:	None known
Dangerous reactions:	None known
Dangerous products of decomposition:	None known
Chemical stability:	Stable
Hazard decomposition products:	None known

#### 11. TOXICOLOGICAL INFORMATION

Acute Toxicity:	Not determined
Primary Irritant Effect	
Skin:	Irritation of skin and mucous membranes.
Eyes:	Irritation effect
Additional Information:	When the product is used or handled to specifications it does not have any harmful effects to our knowledge.

#### 12. ECOLOGICAL INFORMATION

Additional Information:	Complete information is not yet available..
-------------------------	---

#### 13. DISPOSAL CONSIDERATIONS

Proper Shipping Name:	Latex based Acrylic Sealant.
Classification:	No dangerous goods under the transport regulation.
Product Recommendation:	Disposal must be made according to official regulations.
European Waste Catalogue:	08 04 10 - Waste adhesives and sealants other than those mentioned in 08 04 09.
Uncleaned Packaging Recommendation:	Disposal must be made according to official regulations.

#### 14. TRANSPORTATION INFORMATION

Land Transport (ADR/ RID):	Not Applicable
Maritime Transport (IMDG):	Not Applicable
Air Transport (ICAO):	Not Applicable

#### 15. REGULATORY INFORMATION

Labelling according to EC guidelines:	This product is not subject to the labelling requirements of the EC directives.
---------------------------------------	---

## MATERIAL SAFETY DATA SHEET TRADESMAN GAP FILLER

DATE: 26/08/2011

### 16. OTHER INFORMATION

**Additional information:**

The information in this MSDS is based on our present knowledge to the date of this publication. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. It is only a guide for safe handling, use, storage, transporting and disposal of the product.

This document is in accordance to 1907/2006/EC, Article 31